LITHIUM-ION BATTERIES

100AH 12 VOLT

BB10012 BBGC2

50AH/75AH 12 VOLT

BB1250 BB1275

270AH 12 VOLT

BB8D BBGC3

50AH 24 VOLT

BB5024

2-3X MORE POWER

Two to three times more power in the same physical space*

LASTS 10X LONGER

Ten times longer lifespan*

5X FASTER CHARGING

Charge five times faster*

1/5 THE WEIGHT

~ 1/5 the weight for the same amount of usable power

DROP-IN REPLACEMENT

Easy drop-in replacement for lead acid batteries

100% DEPTH OF DISCHARGE

Use all of your battery with 100% depth of discharge and no memory effect

SELF HEATED

Available with optional self-heating function

10 YEAR WARRANTY

Industry-leading warranty and service

**versus traditional lead acid batteries*

BATTLEBORNBATTERIES.COM

dragonfly® ENERGY

PRODUCT SPECIFICATIONS

BATTERY	AMP & VOLTAGE	CHARGING VOLTAGE	FLOAT VOLTAGE	WEIGHT	DIMENSIONS
BB10012	100AH 12V	14.2V - 14.6V	13.4V - 13.8V	31LBS	12.76" X 6.86" X 8.95"
BB5024	50AH 24V	28.4V - 29.2V	26.8V - 27.6V	31LBS	12.76" X 6.86" X 8.95"
BB1250	50AH 12V	14.2V - 14.6V	13.4V - 13.8V	22LBS	10.49" X 7.11" X 8.93"
BB1275	75AH 12V	14.2V - 14.6V	13.4V - 13.8V	27LBS	10.49" X 7.11" X 8.93"
BBGC2	100AH 12V	14.2V - 14.6V	13.4V - 13.8V	31LBS	10.31" X 7.28" X 11.02"
BB8D	270AH 12V	14.2V - 14.6V	13.4V - 13.8V	81LBS	21.29" X 11.59" X 10.01"
BBGC3	270AH 12V	14.2V - 14.6V	13.4V - 13.8V	81LBS	22.83" X 7.09" X 13.15"

LIFESPAN: *3,000 - 5,000 Cycles*

**Cycle life varies widely depending on rate of charge. After 3,000 cycles you will have approximately 75% battery capacity remaining if charging and discharging at a 1C rate. Most applications are less than 0.5C rate, which means you will get more cycles in most applications.*

TEMPERATURE RANGE: *-4˚F to 135˚F*

USA-BASED TECHNICAL SUPPORT & SERVICE YOU CAN COUNT ON!

FULL POWER SYSTEMS & INDIVIDUAL COMPONENTS AVAILABLE!