



SOLAR PANEL

DFE150S-24U


High Efficiency Monocrystalline PV Module

64 CELL
MONOCRYSTALLINE MODULE

150W
POWER OUTPUT

20.00%
MODULE EFFICIENCY

5%
POSITIVE TOLERANCE



- Nominal 24V DC for standard output.
- Outstanding low-light performance.
- Heavy-duty anodized frames.
- High transparent low-iron, tempered glass.
- Designed to withstand high wind pressures, Hail, and heavy snow.
- Quality aesthetic appearance.



High Efficiency

Module Efficiency improved through advanced cell technology and manufacturing capabilities.



High PID Resistance

Advanced cell technology and qualified materials lead to high resistance to PID.




Withstand Harsh Environment

High PID Resistance
5400 Pa positive load
2400 Pa negative load
Salt mist (IEC 61701)

Performance Warranty


10 years
Product Warranty

25 years
Power Warranty



Product Certificate	IEC 61215, IEC61730
Management Certificate	ISO 9001:2016
Other certificate	Fire Rating Class C, TÜV Rheinland
Positive mechanical load	>5400Pa
Positive power tolerance	0~+5W
Warranty information	2 Year Product Warranty and Workmanship








Electrical Characteristics	DFE150S-24U
Product Code	150032401A
Maximum Power (P _{max})	150W
Voltage at P _{max} (V _{mp})	37.05V
Current at P _{max} (V _{mp})	4.16A
Open-circuit Voltage (V _{oc})	42.74A
Short Circuit Voltage (V _{oc})	4.39A
Temperature Coefficient of V _{oc}	-(80±10)mV/°C
Temperature Coefficient of I _{sc}	(0.065±0.015)%/°C
Temperature Coefficient of Power	-(0.5±0.05)%/°C
NOCT (Air 20°C; Sun 0.8kW/m ² wind 1m/s)	47±2°C
Operating Temperature	-40°C to 85°C
Maximum System Voltage	1000V DC
Power Tolerance	±5%


*STC: Irradiance 1000W/m², AM1.5 spectrum, module temperature 25°C

*NOCT: Nominal operating cell temperature (the data is only for reference)

Specifications	DFE150S-24U
Cells	Monocrystalline silicon solar cell
No. of cells and connections	64(4x16)
Module dimension	1140mm[44.88in.]x705mm[27.76in.]x35mm[1.38in.]
Weight	8.98kg[19.80lbs]
Packing information	1190mm[46.85in.]x755mm[29.72in.]x85mm[3.35in.]/(1pc/ctn)



Characteristics



DFE150S-24U I-V Curves

Dimensions in brackets are in inches.
Un-bracketed dimensions are in millimeters.
Unit: mm[in.]