

3 kW Industrial Grade Energy System

The **Battle Born Power Station 3000** is an industrial grade portable energy system built for the toughest jobs and harshest environments. Delivering 3 kW of continuous, pure sine wave output and 2.5 kWh of long-lasting LiFePO₄ energy, it provides clean, quiet, and safe power without the noise or fumes of traditional generators. Engineered with advanced electronics, intelligent power management, and precision-built systems, it ensures reliable performance wherever energy is needed. With integrated heating, weather-sealed construction, and proven durability, this industrial-grade system is built to perform day in and day out without compromise. Proudly assembled in North America.

Key Features

High-Performance LiFePO₄ Battery Technology

Powered by advanced LiFePO₄ chemistry rated for over 3,500 cycles, delivering safe, maintenance-free energy with superior thermal stability and long-term reliability.

Low Maintenance, High Reliability

Battle Born Power Station systems are designed for consistent, worry-free performance—no routine upkeep required. Focus on your work, not your power source.

Integrated Heating System

Automatically regulates internal temperature for reliable operation in extreme cold—maintaining performance down to -22 °F.

Built for the Elements

Engineered to perform consistently across a wide temperature range of -22 °F to 122 °F, ensuring dependable power in both cold and hot environments.

30 Month Warranty

Weather-Sealed & Dust-Resistant Design

Constructed to operate in the harshest environments, from job sites and service vehicles to remote field operations, keeping internal systems protected from dust, debris, and moisture.

Pure Sine Wave Power Output

Delivers clean, stable AC power for sensitive electronics and high-demand tools alike, providing 3 kW on the Power Station Pro 3000.

Three-Way Charging Flexibility

Recharge via solar, vehicle, or grid power with advanced MPPT technology for fast, intelligent charging anywhere work takes you.

Assembled in North America

Proudly assembled and tested in North America to meet demanding safety and performance certifications, including UL9540A, UL1642, and UL1741.

Key Features Case

Smooth, Silent Mobility

Durable polyurethane wheels with stainless-steel bearings roll easily across rough terrain for quiet, effortless transport. Take it further with the optional Off-Road Carrier, designed for heavy-duty mobility over sand, gravel, and uneven ground.

Retractable Handle for Easy Transport

An adjustable two-stage handle ensures comfortable control and portability, even when fully loaded.

Indestructible & Lightweight NK-7 Resin

Impact-resistant and ultra-light, this rugged NK-7 resin shell is designed with reinforced corners and thick walls to absorb shocks and protect critical components in the harshest environments.

Weather-Sealed & Dust-Resistant

Built to keep out rain, dust, and debris so your power system performs flawlessly wherever it's deployed.

Specifications		Category	Power Station Pro 3000
Category	Power Station Pro 3000	Output Voltage Threshold	± 5%
Power Output	3,000W	Dimensions	23.8 × 15.5 × 13.2 in. Lx W x H
Surge Power	4,500W 500ms 6,000W 10ms	Weight	75.6 lb. 34.3 kg
Loaded Motor Capacity	+2 HP	Operating Temperature	−22°F to 122°F −30 °C to 50 °C
Energy Storage	2.5 kWh	Storage Temperature	−22°F to 122°F −30 °C to 50 °C
Battery Chemistry	LiFePO ₄	Recharge Time Grid	2.5 hours
Cycle Life	3,500+ Cycles	Recharge Time Solar	2 hours with maximum solar power
Voltage (AC)	120V AC 240V AC EU	Idle Power Consumption	40W
Frequency	60 Hz 50 Hz EU	Humidity Range	5 % - 95 %
Solar Input Power	1,600 W	Vibration Resistance	IEC 60068-2-64
Solar Input Volt. Range	30 - 80 V DC	Shock Resistance	IEC 60068-2-31
Max Solar Amperage	40A	Output Efficiency	> 90 %
Alternator Input Power	30A	Certifications/Inspections	CE, UL9540A, UL1642, ESA SPE-1000, UL1741
12V DC Accessory	12V regulated DC output up to 160W	Safety Protections	Solar reverse polarity protection, overload protection, short circuit protection, surge
Auto Gen Start (AGS)	Supports generators with two-wire auto- start. Automatically starts the generator at ~15% battery and stops it at ~85%.	Origin	Assembled in North America
Grid Charging Power	1,200W		
Bypass Power	1,200W		ote it is the customer's obligation to check local ents and certification requirements of all Battle



electrical requirements and certification requirements of all Battle Born/Hybrid Power Solutions purchased equipment to ensure they meet the local electrical code. Additional components such as AFCI protection, Conduit Caps, and fusing/breakers may be required.



Sine Wave Output



Pure Sine Wave

Inputs & Outputs



How Long Will it Power My Device?

	Device	Watts	Power Station Pro 3000	
Home	32" LCD TV	50	32 hours	
	Smartphone	10 wh	250 charges	
	Laptop	50 wh	50 charges	
	Refrigerator (Small)	30	80 hours	
	Refrigerator (Large)	60	60 hours	
	Light (High EFF)	5	70 hours	
	Device	Watts	Power Station Pro 3000	
	Device Hammer Drill	Watts	Power Station Pro 3000 3.5 hours*	
				*Trigger time: time spent operating
۵	Hammer Drill	700	3.5 hours*	and using the equipment. Run times do not include standby
strial	Hammer Drill LED Contractor Lights x2	700	3.5 hours* 25 hours	and using the equipment.
Industrial	Hammer Drill LED Contractor Lights x2 Hand Grinder	700 100 450	3.5 hours* 25 hours 5.5 hours*	and using the equipment. Run times do not include standby power used by the power

Manufactured and Supported by Hybrid Power Solutions

Battle Born Industrial Grade Power Stations are manufactured and supported by Hybrid Power Solutions in North America. For Technical Support specific to this product line, please contact: info@hybridps.ca | +1 (866) 549-2743